

Bosch Professional Series: the first choice for Builders.

55°C FACTORY SET UNIT NOW AVAILABLE



The latest project range of Bosch continuous flow hot water systems has been specifically designed for superior quality, high energy efficiency and ease of installation for your building projects.

Whether building a new home, or replacing an existing hot water system as part of a renovation, a **Bosch Professional (21L/min)** or **Bosch Professional Plus (26L/min)** provides uncompromised quality while being compact, space-saving and easy to install.

Key Features:

- ▶ 50°C temperature limited models available - no need for additional tempering valves
- ▶ Professional Plus is also available as a temperature adjustable unit
- ▶ 5.5+ star energy efficiency rating
- ▶ Easy installation
- ▶ Compact design
- ▶ Install up to 4 optional temperature controllers
- ▶ Available in Natural or LP Gas
- ▶ Comprehensive warranties for domestic installations available

For more information call 1300 30 70 37 or visit www.bosch-climate.com.au



BOSCH

Hot Water

Security Bracket

BLB70

Bosch offers a security bracket made from 2mm thick galvanised plate steel which attaches to the wall and the hot water system to secure your investment. Padlock is not included.

Dimensions

Height: 60mm
Width: 175mm
Depth: 35mm



Project Recess Box

PRB50L - Professional
PRB26L - Professional Plus

Ideal for new homes, allows the Bosch Professional or Bosch Professional Plus to be completely recessed, saving space and protecting the appliance. The project recess box can also be painted to suit the appearance of the home.

Brick opening dimensions

Height: 930mm
Width: 345 mm
Depth: 145mm
(minimum dimensions)



Pipe Cover

YPHC304

A pipe cover* can be easily attached to the Bosch Professional or Bosch Professional Plus. It conceals the pipes leading to the appliance, giving a neat and smooth finish to the installation. This allows the power point to be sheltered beneath the cover.

**Available for non-recessed models only*

Dimensions

Height: 410mm
Width: 342mm



Bosch Professional
(21L/min)

Bosch Professional Plus
(26L/min)

Specifications	Model		
	Bosch Professional	Bosch Professional Plus	Bosch Professional Plus 55°C factory set
Part Number	YS2170RA5P	YS2670RA5P	YS2670RAHP
Installation	External	External	External
Ignition	Electronic	Electronic	Electronic
L/min (25°C rise)	21	26	26
Min. operating inlet water pressure (kPa)	100	100	100
Min. constant water pressure for Max flow (kPa)	130	230	230
Max. inlet water pressure (kPa)	1000	1000	1000
MJ/hr	170	200	200
Star Rating	5.56	5.53	5.53
Temperature	50°C limited	50°C limited	Preset at 55°C
Antifrost	Standard	Standard	Standard
Gas Type	NG/LPG	NG/LPG	NG/LPG
Electrical Supply	230-240 VAC 50 Hz (10A weatherproof power point required within 500mm of the unit)		
Temperature Controller	Up to 4 temperature controllers can be installed (Premium Controllers: YPRM67XBN, YPRS67XBN; Sub controller: YPRP62XB)		
Unit Height x Width x Depth (mm)	520x350x170	600x350x170	600x350x170
Carton Weight (kg)	19	22	22
Domestic Warranty			
Parts & Labour	3 Years	3 Years	3 Years
Heat Exchanger (part only)	10 Years	10 Years	10 Years
Pipe Connection Sizes			
Natural Gas	20mm (3/4")	20mm (3/4")	20mm (3/4")
LP Gas	20mm (3/4")	20mm (3/4")	20mm (3/4")
Cold Water	20mm (3/4")	20mm (3/4")	20mm (3/4")
Hot Water	20mm (3/4")	20mm (3/4")	20mm (3/4")

Contact Us: 1300 30 70 37 or visit www.bosch-climate.com.au